

## CYLINDER TYPE EMBROIDERY MACHINE SPECIFICATION SHEET

### MODEL HCG-1206-45TTC

Net Weight (1430 lbs)

Gross Weight (2090 lbs)

Net Height 67.5" X Depth 50" X Width 114" Gross Height 67.3" X Depth 42" X Width 120"

SEWING AREA	WIDTH	HEIGHT	SPEED
Normal Use	360mm (14.0")	450mm (17.7")	300 - 900 spm
Tubular Use	320mm (12.6")	320mm (12.6")	300 - 850 spm
Cap Use (Wide)	360mm (14.0")	Variable	300 - 800 spm
Cap Use (Normal)	135mm (5.3")	83mm (3.2")	300 - 800 spm

**NOTE:** MACHINE SPEED MAY REQUIRE TO BE CHANGED ACCORDING TO EMBROIDERY CONDITIONS.

### STANDARD DEVICES:

- \* Automatic Thread Trimmers
- \* Built in Disk Drive Unit
- \* Design Memory of 259,000 Stitches
- \* Built in Bobbin Winder
- \* Built in Serial RS-232C Interface
- \* Built in Rotary Type Thread Break Sensors

### STANDARD ACCESSORIES:

SQUARE PLASTIC TUBULAR HOOP		
12pcs	PTA-32320-360	320mm (12.6") X 320mm (12.6")
ROUND PLASTIC TUBULAR HOOP		
12pcs	PTA-12-360	120mm (4.7")
12pcs	PTA-15-360	150mm (5.9")
12pcs	PTA-18-360	180mm (7.1")
12pcs	PTA-21-360	210mm (8.2")
CAP FRAME		
12pcs	Wide Cap Frame	360mm (14.0") X Variable
6pcs	Wide Driver	
1pcs	Cap Hooping Gauge	
HOOPING STAND		
1pcs	Table Type	

**NOTE:** SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Texmac, Inc., Charlotte, NC 704-394-0314