

## **CYLINDER TYPE EMBROIDERY MACHINE SPECIFICATION SHEET**

### **MODEL HCG-1502-45TTC**

Net Weight (1080 lbs)

Gross Weight (1540 lbs)

Net Height 67.5" X Depth 50" X Width 77"

Gross Height 70" X Depth 42" X Width 84"

<b>SEWING AREA</b>	<b>WIDTH</b>	<b>HEIGHT</b>	<b>SPEED</b>
Normal Use	500mm (19.7")	450mm (17.7")	300 - 1100 spm
Tubular Use	440mm (17.3")	420mm (16.5")	300 - 1100 spm
Cap Use (Wide)	360mm (14.0")	Variable	300 - 850 spm
Cap Use (Normal)	135mm (5.3")	83mm (3.2")	300 - 850 spm

**NOTE:** MACHINE SPEED MAY REQUIRE TO BE CHANGED ACCORDING TO EMBROIDERY CONDITIONS.

### **STANDARD DEVICES:**

- \* Automatic Thread Trimmers
- \* Built in Disk Drive Unit
- \* Design Memory of 259,000 Stitches
- \* Built in Bobbin Winder
- \* Built in Serial RS-232C Interface
- \* Built in Rotary Type Thread Break Sensors

### **STANDARD ACCESSORIES:**

#### **SQUARE WOODEN TUBULAR HOOP**

4pcs WS-44420-500 440mm (17.3") X 420mm (16.5")

#### **SQUARE PLASTIC TUBULAR HOOP**

4pcs PTA-32320-500 320mm (12.6") X 320mm (12.6")

#### **ROUND PLASTIC TUBULAR HOOP**

4pcs PTA-12-500 120mm (4.7")

4pcs PTA-15-500 150mm (5.9")

#### **CAP FRAME**

4pcs Wide Cap Frame 360mm (14.0") X Variable

2pcs Wide Driver

1pcs Cap Hooping Gauge

#### **HOOPING STAND**

1pcs Table Type

**NOTE:** SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Texmac, Inc., Charlotte, NC 704-394-0314