

## CYLINDER TYPE EMBROIDERY MACHINE SPECIFICATION SHEET

### MODEL HCGX-1204-45TTC

Net Weight (1364 lbs)

Gross Weight (2024 lbs)

Net Height 67.5" X Depth 43" X Width 112"

Gross Height 67" X Depth 50" X Width 122"

SEWING AREA	WIDTH	HEIGHT	SPEED
Normal Use	500mm (19.7")	450mm (17.7")	300 - 900 spm
Tubular Use	420mm (16.5")	440mm (17.3")	300 - 850 spm
Cap Use (Wide)	360mm (14.0")	Variable	300 - 800 spm
Cap Use (Normal)	135mm (5.3")	83mm (3.2")	300 - 800 spm

**NOTE:** MACHINE SPEED MAY REQUIRE TO BE CHANGED ACCORDING TO EMBROIDERY CONDITIONS.

### STANDARD DEVICES:

- \* Automatic Thread Trimmers
- \* Built in Disk Drive Unit
- \* Design Memory of 259,000 Stitches
- \* Built in Bobbin Winder
- \* Built in Serial RS-232C Interface
- \* Built in Rotary Type Thread Break Sensors

### STANDARD ACCESSORIES:

#### SQUARE WOODEN TUBULAR HOOP

8pcs WS-44420-500 440mm (17.3") X 420mm (16.5")

#### SQUARE PLASTIC TUBULAR HOOP

8pcs PTA-32320-500 320mm (12.6") X 320mm (12.6")

#### ROUND PLASTIC TUBULAR HOOP

8pcs PTA-12-500 120mm (4.7")

8pcs PTA-15-500 150mm (5.9")

8pcs PTA-18-500 180mm (7.1")

#### CAP FRAME

8pcs Wide Cap Frame 360mm (14.0") X Variable

4pcs Wide Driver

1pcs Cap Hooping Gauge

#### HOOPING STAND

1pcs Table Type

**NOTE:** SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Texmac, Inc., Charlotte, NC 704-394-0314