CYLINDER TYPE EMBROIDERY MACHINE SPECIFICATION SHEET

MODEIHCGX-1506-45TTC

Net Weight (2145lbs) Gross Weight (2860lbs)
Net Height 67.5" X Depth 43" X Width 155" Gross Height 67" X Depth 50" X Width 165"

SEWING AREA	**WIDTH**	**HEIGHT**	**SPEED**
Normal Use	500mm (19.7")	450mm (17.7")	300 - 900 spm
Tubular Use	420mm (16.5")	440mm (17.3")	300 - 850 spm
Cap Use (Wide)	360mm (14.0")	Variable	300 - 800 spm
Cap Use (Normal)	135mm (5.3")	83mm (3.2")	300 - 800 spm

NOTE: MACHINE SPEED MAY REQUIRE TO BE CHANGED ACCORDING TO EMBROIDERY CONDITIONS.

STANDARD DEVICES:

* Automatic Thread Trimmers
* Built in Disk Drive Unit
* Desgin Memory of 259,000 Stitchs
* Built in Bobbin Winder
* Built in Serial RS-232C Interface
* Built in Rotary Type Thread Break Sensors

STANDARD ACCESSORIES:

SQUARE WOODEN TUBULAR HOOP
12pcs WS-44420-500 440mm (17.3") X 420mm (16.5")
SQUARE PLASTIC TUBULAR HOOP
12pcs PTA-32320-500 320mm (12.6") X 320mm (12,6")
ROUND PLASTIC TUBULAR HOOP
12pcs PTA-12-500 120mm (4.7")
12pcs PTA-15-500 150mm (5.9")
12pcs PTA-18-500 180mm (7.1")
CAP FRAME
12pcs Wide Cap Frame 360mm (14.0") X Variable
6pcs Wide Driver
1pcs Cap Hooping Guage
HOOPING STAND
1pcs Table Type

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Texmac, Inc., Charoltte, NC 704-394-0314